

The Institute of Radio Engineers

REPORT OF THE COMMITTEE ON STANDARDIZATION FOR 1926



DEFINITIONS OF TERMS STANDARD GRAPHICAL SYMBOLS USED IN RADIO ENGINEERING

COPYRIGHT, 1926

BY

The Institute of Radio Engineers
(INC.)

37 WEST 39TH STREET
NEW YORK CITY

PRICE TO NON-MEMBERS, \$1.00 PER COPY

P BORSI

Borri

The Institute of Radio Engineers

REPORT

OF THE

COMMITTEE ON STANDARDIZATION

FOR

1926



DEFINITIONS OF TERMS
STANDARD GRAPHICAL SYMBOLS
USED IN RADIO ENGINEERING

COPYRIGHT, 1926

BY

The Institute of Radio Engineers
(INC.)

37 WEST 39TH STREET
NEW YORK CITY

PRICE TO NON-MEMBERS, \$1.00 PER COPY

COPYRIGHT, 1926
BY
The Institute of Radio Engineers
INC.

The Institute of Radio Engineers

REPORT OF THE COMMITTEE ON STANDARDIZATION

1926

CONTENTS

	PAGE
Preface	2
Definitions of Terms Used in Radio Engineering	5
Section 1—Waves and Wave Propagation	5
Section 2—Transmitting	7
Section 3—Receiving	11
Section 4—Vacuum Tubes	13
Section 5—Circuit Elements and Properties	19
Section 6—Antennas	27
Section 7—Direction Finding	30
Standard Graphical Symbols	31
Index	34

PREFACE

The first standardization report of the Institute of Radio Engineers was issued in 1913. This was succeeded by revised reports issued in 1915 and 1922. Since the publication of the Report of the Committee on Standardization for 1922, the Committee has been engaged in a complete revision of that report which it now presents to the membership of the Institute of Radio Engineers and others concerned with the subject. This report was adopted by the Board of Direction of the Institute on December 1, 1925.

The membership of the Committee on Standardization during the last three years has been as follows:

1923

Donald McNicol, *Chairman*

E. F. W. Alexanderson	J. V. L. Hogan
O. B. Blackwell	H. W. Nichols
L. W. Chubb	A. E. Reoch
J. H. Dellinger	M. B. Sleeper
E. D. Forbes	Bowden Washington
A. N. Goldsmith	L. E. Whittemore

1924

Donald McNicol, *Chairman*

E. H. Armstrong	C. A. Hoxie
L. W. Chubb	F. H. Kroger
J. H. Dellinger	J. H. Morecroft
Lloyd Espenschied	H. W. Nichols
A. N. Goldsmith	R. H. Langley
R. F. Gowan	A. E. Reoch
L. A. Hazeltine	C. H. Taylor
Guy Hill	Bowden Washington
J. V. L. Hogan	L. E. Whittemore

1925

Ralph Bown, *Chairman*

F. P. Andrews	F. A. Kolster
E. H. Armstrong	F. H. Kroger
W. R. G. Baker	R. H. Langley
M. C. Batsel	C. W. Latimer
Edward Bennett	George Lewis
W. W. Brown	R. T. S. Lowell
L. W. Chubb	Donald McNicol
F. C. Conrad	R. H. Marriott
J. H. Dellinger	J. H. Morecroft
F. W. Dunmore	H. W. Nichols
Melville Eastham	A. A. Oswald
Lloyd Espenschied	G. W. Pickard
H. M. Freeman	A. E. Reoch
A. N. Goldsmith	C. E. Speaker
W. A. Graham	C. H. Taylor
L. A. Hazeltine	H. M. Turner
R. A. Heising	Bowden Washington
J. V. L. Hogan	W. C. White
C. A. Hoxie	L. E. Whittemore
C. B. Jolliffe	C. A. Wright

During 1924 and 1925, the Committee organized several sub-committees each of which prepared drafts of definitions for terms employed in a certain specialized part of the radio field. The names of these sub-committees and their chairmen are as follows:

A. E. Reoch, <i>Chairman Sub-committee on Radio Telegraph Transmitter Terminology.</i>	
R. H. Langley, <i>Chairman Sub-committee on Radio Telegraph Receiver Terminology.</i>	
H. W. Nichols	} <i>Joint Chairmen Sub-committee on Radio Telephone Transmitter and Receiver Terminology.</i>
Lloyd Espenschied	
L. A. Hazeltine, <i>Chairman Sub-committee on Vacuum Tube Terminology.</i>	
C. H. Taylor, <i>Chairman Sub-committee on Antenna Terminology.</i>	
L. E. Whittemore, <i>Chairman Sub-committee on Direction Finding Terminology.</i>	

In preparing this report the Committee has recognized the growth in the use of radio by including many terms which were not included in previous reports, but which have either come recently into general use or have become a recognized part of the nomenclature in specialized parts of the radio field. It is hoped, therefore, that this report will be helpful to radio engineers and others by giving such terms and definitions as have gained recognized standing in special branches of radio engineering as well as by indicating what is considered to be good usage of terms in radio literature generally. Trade names have not been included.

The list of terms and definitions has been divided into seven groups in order to facilitate reference to terms which are related to one another in meaning or in use. An alphabetical index is appended.

It was found unnecessary to make any extensive revision of the section giving standard graphical symbols, though a few modifications which were felt to be desirable have been incorporated.

It has been the aim of the Committee to make the report descriptive and explanatory rather than to make the definitions rigorously exact in their phraseology.

The Institute will welcome comments and criticisms which will be helpful in the preparation of revised report in the course of the next two years.

Communications dealing with this work as well as with other Institute matters should be addressed to the Secretary of the Institute of Radio Engineers, 37 West 39th Street, New York City.

DEFINITION OF TERMS USED IN RADIO ENGINEERING

SECTION I—WAVES AND WAVE PROPAGATION

1001. **Wave**—(a) A propagated disturbance, usually periodic; as, an electric wave or a sound wave.
(b) A single cycle of such a disturbance.
(c) A periodic variation as represented by a graph.
1002. **Wavelength**—The distance traveled in one period or cycle by a periodic disturbance. The distance between corresponding phases of two consecutive waves of a wave train. The quotient of velocity by frequency.
1003. **Continuous Waves**—Alternating electric waves in space, of constant amplitude and frequency. (Abbreviation—cw.)
1004. **Modulated Continuous Waves**—Continuous waves of which the amplitude or frequency is repeatedly varied in accordance with a signal wave.
1005. **Key=Modulated Continuous Waves**—Continuous waves of which the amplitude or frequency is varied by the operation of a transmitting key in accordance with the characters of a communicating code.
1006. **Interrupted Continuous Waves**—Waves obtained by the interruption at audio frequency in a periodic manner of an otherwise continuous wave. (Abbreviation—icw.)
1007. **Damped Waves**—Electromagnetic waves proceeding in wave trains in each of which the amplitude progressively diminishes in successive cycles.
1008. **Signal**—The intelligence, message, or effect conveyed in communication.
1009. **Signal Wave**—A wave, the form of which conveys a signal.
1010. **Carrier Wave**—The component of a modulated wave which has the same frequency as the original unmodulated wave. (See 2005, Carrier Current.)
1011. **Radio Field Intensity**—The root-mean-square value of the electric or magnetic field intensity at a point due to

the passage of radio waves. It is often expressed in microvolts per meter.

- 1012. Radio Noise Field Intensity**—A measure of the field intensity, at a point (as a radio receiving station), of electromagnetic waves of an interfering character. In practice the quantity measured is not the field intensity of the interfering waves, but some quantity which is proportional to or bears a known relation to the field intensity.
- 1013. Signal=Noise Ratio**—The ratio at a point of the field intensity of the radio wave to the radio noise field intensity.
- 1014. Strays**—Electromagnetic disturbances in radio reception other than those produced by radio transmitting systems.
- 1015. Static**—Conduction or charging current in an antenna resulting from physical contact between the antenna and charged bodies or masses of gas.
In the United States this term has come to be used quite generally as a synonym for atmospherics.
- 1016. Atmospherics**—Strays produced by atmospheric conditions.
- 1017. Atmospheric Absorption**—A loss of power in transmission of radio waves due to a dissipation in the atmosphere.
- 1018. Transmission Loss**—The loss of power suffered by a transmitted wave in passing along a transmission path or through a circuit device. (See 5076, Transmission—Frequency Characteristic.)
- 1019. Attenuation**—The reduction in power of a wave or a current with increasing distance from the source of transmission.
- 1020. Fading**—The variation of the signal intensity received at a given location from a radio transmitting station as a result of changes in the transmission path. (See 5077, Distortion.)
- 1021. Swinging**—The variation in intensity of a received radio signal resulting from changes in the frequency of the transmitted waves.

SECTION 2—TRANSMITTING

- 2001. Radio Communication**—The transmission of signals by means of radiated electromagnetic waves originating in a constructed circuit.
- 2002. Broadcasting**—The transmission of music, news, entertainment or other intelligence intended for general reception.
- 2003. Radiate**—To emit electromagnetic waves into space.
- 2004. Radiation**—The process of emitting electromagnetic waves into space.
- 2005. Carrier Current**—An alternating current which is modulated by a signal. Ordinarily refers to wire transmission of high-frequency currents. (See 10101, Carrier Wave.)
- 2006. Carrier Frequency**—Frequency of a carrier wave or a carrier current.
- 2007. Carrier Suppression**—That method of operation in which the carrier wave or carrier current is not transmitted.
- 2008. Band of Frequencies**—A continuous range of frequencies extending between two definite frequencies. (See 2012, Radio Channel and 5002, Frequency.)
- 2009. Side Bands**—The bands of frequencies, one on either side of the carrier frequency, produced by the process of modulation.
- 2010. Side Frequencies**—The frequency on either side of the carrier frequency produced by the process of single frequency modulation.
- 2011. Single-Side-Band Transmission**—That method of operation in which one side band is transmitted, and the other side band is suppressed. The carrier wave may be either transmitted or suppressed.
- 2012. Radio Channel**—A band of frequencies or wave lengths of a width sufficient to permit of its use for radio communication. The width of a channel depends upon the type of transmission. (See 2008, Band of Frequencies.)
- 2013. Radio Transmitting Set (Transmitter)**—A device for producing radio-frequency power and modifying it in accordance with a signal.
- 2014. Vacuum Tube Transmitter**—A radio transmitter in which vacuum tubes are utilized to convert the applied electric power into radio-frequency power.

- 2015. Oscillator**—A non-rotating device for producing alternating current, the output frequency of which is determined by the characteristics of the device. (See 2018, Radio-Frequency Alternator.)
- 2016. Master Oscillator**—An oscillator of comparatively low power so arranged as to control the frequency of the output of an amplifier.
- 2017. Tank Circuit**—An intermediate oscillatory circuit associated with the output circuit of a vacuum tube transmitter which absorbs the output of the vacuum tube transmitter in the form of energy impulses of high value and short duration and delivers the power to the load in substantially sinusoidal form.
- 2018. Alternator Transmitter**—A radio transmitter which utilizes radio-frequency currents generated by a radio-frequency alternator.
- 2019. Radio-Frequency Alternator**—A rotating-type alternating-current generator which generates radio-frequency currents. (See 2014, Oscillator.)
- 2020. Load Compensator**—Part of a radio-frequency alternator speed regulator consisting of a device to vary the torque of the motor driving a radio-frequency alternator approximately in accordance with variations of the load on the motor.
- 2021. Arc Converter**—A form of oscillator comprising an electric arc used for the conversion of direct to alternating or pulsating current.
- 2022. Spark Transmitter**—A radio transmitter which utilizes the oscillatory discharge of a condenser through an inductance and a spark gap as the source of its radio-frequency power.
- 2023. Plain Antenna Transmitter**—A spark transmitter in which the spark gap is connected directly in the antenna circuit.
- 2024. Spark Gap**—An arrangement of electrodes, used for closing a circuit (usually oscillatory) at a predetermined voltage. The several types of spark gaps are:
- (a) **Plain Gap**—A spark gap between two fixed metal electrodes.
- (b) **Rotary Gap**—Spark gap in which one of the electrodes is a rotating element which causes a regular change in gap

length thereby timing the beginning of the discharge and modifying its duration.

- (c) **Synchronous Rotary Gap**—A rotary gap in which the speed of rotation is such that the discharge is synchronous with the alternating voltage applied.
- (d) **Quenched Gap**—A spark gap in which the strongly damped discharge current is quickly stopped by the quenching or extinction of the spark.
- 2025. Impulse Excitation**—A method of producing damped oscillatory current in a circuit in which the duration of the impressed voltage is short compared with the duration of the current produced.
- 2026. Frequency Changer**—A device delivering alternating current at a frequency which differs from the frequency of the supply current.
- 2027. Frequency Multiplier**—A frequency changer used to multiply by an integer the frequency of an alternating current.
- 2028. Telephone Transmitter**—A sound operated device designed to produce an alternating current the form of which corresponds to that of the sound wave actuating it.
- 2029. Microphone**—A telephone transmitter comprising a contact device designed to have its electrical resistance directly and materially altered by slight differences in mechanical pressure.
- 2030. Condenser Transmitter**—A telephone transmitter, the operation of which involves a variation in electrostatic capacity produced by a sound wave.
- 2031. Modulation**—The process whereby the frequency or amplitude of a wave is varied in accordance with a signal wave.
- 2032. Double Modulation**—The process of modulation in which a carrier wave of one frequency is first modulated by the signal wave and is then made to modulate a second carrier wave of another frequency.
- 2033. Percentage Modulation**—The variation in amplitude of a modulated wave from its mean value expressed in per cent. of the mean value.
- 2034. Modulator**—A device to effect the process of modulation. It may be operated by virtue of some non-linear characteristic or by a controlled variation of some circuit quantity.

- 2035. Magnetic Modulator (Ferromagnetic Modulator)**—A magnetic device employed as a modulator and functioning by virtue of its non-linear magnetization characteristic.
- 2036. Vacuum Tube Modulator**—A modulator employing a vacuum tube as a modulating element.
- 2037. Duplex Operation**—The operation of associated radio transmitting and radio receiving channels in which transmission and reception are simultaneous.

SECTION 3—RECEIVING

- 3001. Receiving Set (Receiver)**—A device for converting radio waves into perceptible signals.
- 3002. Monitoring Receiver**—A receiver arranged to enable an operator to check the operation of a transmitting set.
- 3003. Heterodyne Reception**—The process of receiving radio waves by combining the received current with locally generated alternating current. The locally generated frequency is commonly different from the frequency of the received current, thus producing beats. This is called beat reception.
- 3004. Self-Heterodyne Reception (Autodyne Reception)**—A system of heterodyne reception through the use of a device which is both an oscillator and a detector.
- 3005. Homodyne Reception**—The process of detecting a wave by the aid of a locally generated wave of carrier frequency. (Sometimes called zero-beat reception.)
- 3006. Super-Heterodyne Reception**—A method of reception in which the received current is combined with the current from a local oscillator and converted into current of an intermediate frequency which is then amplified and detected to reproduce the original signal wave.
- 3007. Intermediate Frequency**—A frequency of a magnitude between that of the carrier employed in radio transmission and the frequency of modulation, and to which the carrier is converted in the super-heterodyne process of reception.
- 3008. Reflex Circuit**—An arrangement in which one or more amplifiers are used, each to amplify the signal both before and after detection.
- 3009. Tuning**—Primarily, the adjustment of a circuit or circuits to resonance. Use also to mean the adjustment of a circuit or system to secure maximum transmission of a desired signal.
- 3010. Sensitivity**—The degree to which a radio receiving set responds to signals of the frequency to which it is tuned.
- 3011—Selectivity**—The degree to which a radio receiving set is capable of differentiating between signals of different frequencies.
- 3012. Detector**—That portion of the receiving apparatus which, connected to a circuit carrying currents of radio frequency, and in conjunction with a self-contained or separate indicator, translates the radio-frequency power into a form suitable

for operation of the indicator. This translation may be effected either by the conversion of the radio-frequency power, or by means of the control of local power. The indicator may be a telephone receiver, relaying device, tape recorder, and so on.

The most common type of detector is a vacuum tube operated on a non-linear portion of its characteristic curve, thereby converting a modulated radio-frequency current into a modulated direct current.

A tube which operates similarly to a detector tube, but the output of which does not operate an indicator, may properly be called a frequency converting tube. (See 5062; Rectifier.)

3013. Detection Coefficient—The quotient of the direct current in a radio detector with no external resistance, due to an impressed alternating voltage, divided by the square of the r.m.s. alternating voltage. As most precisely used, the term refers to a voltage so small that its value is independent of the magnitude of the voltage, in which case it is expressed by the equation.

$$\text{Detection Coefficient} = \frac{1}{2} \frac{d^2 i}{d e^2}$$

where e and i are respectively the voltage and current as taken from the characteristic curve of the detector with no external resistance. (See 4015, Grid Detection Coefficient and 4039, Mutual Detection Coefficient.)

3014. Telephone Receiver—An electrically operated device designed to produce sound waves which correspond to the signal current actuating it.

3015. Loud Speaker—A telephone receiver designed to produce sound of sufficiently large volume to be heard at a substantial distance.

3016. Interference—Confusion of reception due to strays, undesired signals or other causes; also that which produces the confusion.

SECTION 4—VACUUM TUBES

4001. Vacuum Tube—A device consisting of a number of electrodes contained within an enclosure evacuated to a low pressure. This term is also commonly used less broadly in referring to the type of vacuum tube having grid, plate and filament (triode).

4002. Diode—A type of vacuum tube containing two electrodes which passes current wholly or predominantly in one direction.

Note—A vacuum tube having a single cathode and two anodes which operate alternately may properly be called a **double diode**.

4003. Triode—A type of vacuum tube containing an anode, a cathode and a third electrode, in which the current flowing between the anode and the cathode is controlled by the relative potential of the third or control electrode.

4004. Cathode—The electrode to which the current flows through the vacuous space. The cathode is usually the source of the electron emission which constitutes this current. (See 4005, Filament.)

4005. Filament—The cathode in the common type of vacuum tube (triode).

4006. Filament Voltage—The voltage between the terminals of the filament.

4007. Filament Current—The current supplied to the filament to heat it.

Note—When the filament is heated by direct current which is not large in comparison with the plate current, the filament current is ordinarily measured at that filament terminal where it is the larger.

4008. Control Electrode—The electrode, the relative potential of which controls the current flowing between the anode and the cathode. (See 4009, Grid.)

4009. Grid—The common name for the control electrode in a vacuum tube.

4010. Grid Potential—The electric potential of the grid relative to the cathode. (See note under 4020, Plate Potential.)

4011. Grid Current—The conduction current passing from the grid through the vacuous space.

4012. Reversed Grid Current—The conduction current passing to the grid through the vacuous space.

4013. Grid Conductance—The quotient of the change in grid current divided by the change in grid potential producing it, under the condition of constant plate potential. As most precisely used, the term refers to infinitesimal changes, as indicated in the defining equation

$$\text{Grid conductance, } g_g = \frac{d i_g}{d e_g}, \quad e_p = \text{const.}$$

Note—The grid conductance is the resistive component of the input admittance of the vacuum tube.
(See 4024, Plate Conductance.)

4014. Grid Characteristic Curve—The curve plotted between grid potential as abscissa and grid current as ordinate. (See 4026, Plate Characteristic Curve; 4040, Mutual Characteristic Curve and 4043, Emission Characteristic Curve.)

4015. Grid Detection Coefficient—The quotient of the change in the direct grid current produced in a vacuum tube with no external grid or plate resistance, due to an impressed alternating grid voltage, divided by the square of the r.m.s. alternating voltage. As most precisely used, the term refers to a grid voltage so small that its value is independent of the magnitude of the voltage, in which case it is expressed by the equation

$$\text{Grid detection coefficient} = \frac{1}{2} \frac{d^2 i_g}{d e_g^2}, \quad e_p = \text{const.}$$

where e_g and i_g are respectively the grid potential and the grid current.

(See 3013, Detection Coefficient and 4039, Mutual Detection Coefficient.)

4016. Grid Condenser—A condenser connected in series in the grid or control circuit of a vacuum tube.

4017. Grid Leak—A resistor usually of very high resistance, used in association with a condenser and connected directly or indirectly between the cathode and the grid of a vacuum tube.

4018. Anode—The electrode from which the current flows through the vacuous space. (See 4019, Plate.)

4019. Plate—The common name for the anode in a vacuum tube.

4020. Plate Potential—The electric potential of the plate relative to the cathode.

Note—If the cathode is a filament heated by direct

current, its negative terminal is ordinarily taken as the datum of potential; if heated by alternating current, its mid-point is taken as the datum.

4021. Plate Current—The conduction current passing from the plate through the vacuous space.

4022. Amplification Factor—A measure of the effectiveness of the grid potential relative to that of the plate potential in affecting the plate current; it is the quotient of the change in plate potential divided by the negative change in grid potential, under the condition that the plate current remains unchanged. As most precisely used, the term refers to infinitesimal changes in the potentials as indicated in the defining equation

$$\text{Amplification factor } \mu = -\frac{d e_p}{d e_g}, \quad i_p = \text{const.}$$

(See 5044, Voltage Amplification.)

4023. Mutual Conductance—The quotient of the change in plate current divided by the change in grid potential producing it, under the condition of constant plate potential. As most precisely used, the term refers to infinitesimal changes, as indicated in the defining equation

$$\text{Mutual conductance, } g_m = \frac{d i_p}{d e_g}, \quad e_p = \text{const.}$$

The unit ordinarily used is the micromho.

Note—In rare cases, when the dependence of the grid current on the plate potential is to be considered, the following terms and symbols may be employed:

Inverse amplification factor

$$\mu_n = -\frac{d e_g}{d e_p}, \quad i_g = \text{const.}$$

Inverse mutual conductance,

$$g_n = \frac{d i_g}{d e_p}, \quad e_g = \text{const.}$$

(See 4040, Mutual Characteristic Curve.)

4024. Plate Conductance—The quotient of the change in plate current divided by the change in plate potential producing it, under the condition of constant grid potential. As most precisely used, the term refers to infinitesimal changes, as indicated in the defining equation

Plate conductance, $g_p = \frac{d i_p}{d e_p}$, $e_g = \text{const.}$

Note—The plate conductance is the resistive component of the internal output admittance of a vacuum tube. (See 4013, Grid Conductance.)

4025. Plate Resistance—The reciprocal of the plate conductance.

$$r_p = \frac{1}{g_p} = \frac{d e_p}{d i_p}, e_g = \text{const.}$$

Note—The following relations exist between the terms numbered 4022, 4023, 4024 and 4025.

$$g_m = \mu g_p = \frac{\mu}{r_p}$$

4026. Plate Characteristic Curve—The curve plotted between plate potential as abscissa and plate current as ordinate. (See 4014, Grid Characteristic Curve; 4040, Mutual Characteristic Curve and 4043, Emission Characteristic Curve.)

4027. Plate Choke Coil—A coil of relatively high inductance inserted in the anode supply circuit of a vacuum tube amplifier, modulator, or oscillator to maintain substantially constant current in this circuit throughout a cycle of the amplified or generated current.

4028. Filament Capacity (C_f)—The sum of the direct capacities between the filament and all other conductors of a vacuum tube.

4029. Grid Capacity (C_g)—The sum of the direct capacities between the grid and all other conductors of a vacuum tube.

4030. Plate Capacity (C_p)—The sum of the direct capacities between the plate and all other conductors of a vacuum tube.

4031. Direct Capacity (C)—between two conductors—The quotient of the charge produced on one conductor by the voltage between it and the other conductor divided by this voltage, all other conductors in the neighborhood being at the potential of the first conductor.

4032. Grid-Plate Capacity (C_{gp})—The direct capacity between the grid and the plate.

4033. Grid-Filament Capacity (C_{gf})—The direct capacity between the grid and the filament (See 4032, Grid-Plate Capacity.)

4034. Plate-Filament Capacity (C_{pf})—The direct capacity between the plate and the filament. (See 4032, Grid-Plate Capacity.)

Note—All capacities are ordinarily understood to be taken with the vacuum tube in its completed form but not in its socket or other holder.

Note—The capacities C_{pf} , C_{gf} and C_{gp} are not those ordinarily directly measured, but are computed from the direct capacities which can be directly measured, in accordance with the following equations:

$$C_f = C_{gf} + C_{pf}; C_p = C_{pf} + C_{gp}; C_g = C_{gf} + C_{gp};$$

$$C_{pf} = \frac{C_p + C_f - C_g}{2}; C_{gf} = \frac{C_g + C_f - C_p}{2}; C_{gp} = \frac{C_g + C_p - C_f}{2}$$

4035. Internal Output Impedance (of any electrical device having output terminals)—The quotient of the alternating voltage impressed on the output terminals divided by the alternating current thereby produced at these terminals, in the absence of impressed alternating voltages at other points.

Note—This is sometimes called simply “output impedance,” but the prefix “internal” is preferred in order more surely to distinguish it from the impedance of the external output circuit.

4036. Internal Output Admittance—The reciprocal of internal output impedance.

4037. Input Impedance (of any electrical device)—The quotient of the alternating voltage impressed on the input terminals of the device divided by the alternating current thereby produced at these terminals, in the absence of impressed alternating voltages at other points.

4038. Input Admittance—The reciprocal of input impedance.

4039. Mutual Detection Coefficient of a vacuum tube—The quotient of the change in the direct plate current produced in a triode with no external grid or plate resistance, due to an impressed alternating grid voltage, divided by the square of the r.m.s. alternating voltage. As most precisely used, the term refers to a grid voltage so small that its value is independent of the magnitude of the voltage, in which case it is expressed by the equation

$$\text{Mutual detection coefficient} = \frac{1}{2} \frac{d^2 i_p}{d e_g^2}, e_p = \text{const.}$$

(See 3013, Detection Coefficient and 4015, Grid Detection Coefficient.)

- 4040. Mutual Characteristic Curve (Grid=Plate Characteristic Curve)**—The curve plotted between the grid voltage as abscissa and the plate current as ordinate. (See 4014, Grid Characteristic Curve; 4023, Mutual Conductance; 4026, Plate Characteristic Curve and 4043, Emission Characteristic Curve.)
- 4041. Electron Emission**—The phenomenon of the liberation of electrons from the surface of a body into the surrounding space, usually under the influence of heat, ultra-violet rays, x-rays, impact excitation, or chemical disintegration.
- 4042. Emission Current**—The value of the current carried by electrons emitted from a cathode under the influence of a voltage such as will draw away all the electrons emitted.
- 4043. Emission Characteristic Curve**—The curve plotted between a factor controlling electron emission (such as the temperature, voltage or current of the cathode or filament) as abscissa and the emission current from the cathode or filament as ordinate. (See 4014, Grid Characteristic Curve; 4026, Plate Characteristic Curve and 4040, Mutual Characteristic Curve.)
- 4044. Thermionic**—Relating to electron emission under the influence of heat.

SECTION 5—CIRCUIT ELEMENTS AND PROPERTIES

- 5001. Cycle**—One complete set of positive and negative values of an alternating current.
- 5002. Frequency**—The number of cycles per second. (See 2008, Band of Frequencies.)
- 5003. Kilocycle** (strictly kilocycle per second or cycle per millisecond)—A thousand cycles per second.
- 5004. Megacycle** (strictly megacycle per second or cycle per microsecond)—A million cycles per second.
- 5005. Audio Frequencies**—The frequencies corresponding to normally audible sound waves. The upper limit ordinarily lies between 10,000 and 20,000 cycles.
- 5006. Radio Frequencies**—The frequencies higher than those corresponding to normally audible sound waves. (See 5005, Audio Frequencies.)
- Note**—It is not implied that radiation cannot be secured at lower frequencies, nor that radio frequencies are necessarily above the limit of audibility.
- 5007. Group Frequency**—The number of trains of damped waves or current per second.
- Note**—The term "group frequency" has replaced the term "spark frequency."
- 5008. Resonance Frequency** (of a circuit)—The frequency at which the supply current and supply voltage of the circuit are in phase.
- 5009. Frequency Meter**—An instrument for measuring frequency. (Frequency meters used in radio work are sometimes called wavemeters.)
- 5010. Fundamental Frequency**—That frequency of which all component frequencies are integral multiples.
- 5011. Fundamental Wavelength**—The wavelength corresponding to fundamental frequency.
- 5012. Harmonic**—A component of a periodic quantity having a frequency which is an integral multiple of the fundamental wave frequency. For example, a component, the frequency of which is twice the fundamental frequency, is called the second harmonic.
- 5013. Periodic Current**—Periodically reversing current the frequency of which is determined by the electrical constants of the circuits in which it flows. It may be either damped or continuous.

- 5014. Oscillatory Circuit**—A relatively low resistance circuit containing both inductance and capacity, such that a voltage impulse will produce a current which periodically reverses.
- 5015. Beating**—A phenomenon in which two or more periodic quantities of not greatly different frequencies react with each other to produce a resultant having pulsations of amplitude.
- 5016. Beat**—A complete cycle of such pulsations.
- 5017. Beat Frequency**—The number of beats per unit of time. This frequency is equal to the difference between the frequencies of the combining waves.
- 5018. Series Resonance**—A condition which exists in a circuit having inductance and capacity connected in series, when the supply current and supply voltage are in phase.
- 5019. Parallel Resonance**—A condition which exists in a circuit having inductance and capacity connected in parallel, when the supply current and supply voltage are in phase.
- 5020. Acceptor**—A circuit having inductance and capacity so arranged and tuned as to offer low impedance to currents of a given frequency, and high impedance to currents of any other frequency. (See 5021, Rejector.)
- 5021. Rejector**—A circuit having inductance and capacity so arranged and tuned as to offer high impedance to the flow of currents of a given frequency and low impedance to currents of all other frequencies. (See 5020, Acceptor.)
- 5022. Coupling**—The association of two circuits in such a way that energy may be transferred from one to the other.
- 5023. Coupling Coefficient**—The ratio of the mutual or common impedance component of two circuits to the square root of the product of the total impedance components of the same kind in the two circuits. (Impedance components may consist of inductance, capacity or resistance.)
- 5024. Direct Coupling**—Association of two radio circuits by having an indicator, a condenser, or a resistor, common to both circuits.
- 5025. Inductive Coupling**—The association of one circuit with another by means of inductance common or mutual to both. (This term when used without modifying words is commonly used for coupling by means of mutual inductance, whereas coupling by means of self-inductance common to both circuits is called "direct inductive coupling.")

- 5026. Capacity Coupling**—The association of one circuit with another by means of capacity common or mutual to both.
- 5027. Resistance Coupling**—The association of one circuit with another by means of resistance common to both.
- 5028. Coupler**—An apparatus which is used to transfer radio-frequency power from one circuit to another by associating together portions of these circuits. Couplers are of the same types as the types of coupling—inductive, capacity, and resistance.
- 5029. Coupling Coil**—An inductance coil used as a coupler.
- 5030. Coupling Condenser**—A condenser used to produce coupling between two circuits.
- 5031. Decremeter**—An instrument for measuring the logarithmic decrement of a train of waves.
- 5032. Logarithmic Decrement**—The Napierian logarithm of the ratio of the first to the second of two successive amplitudes in the same direction, for an exponentially damped alternating current. The logarithmic decrement can also be considered as a constant of a simple radio circuit, being π times the product of the resistance by the square root of the ratio of the capacity to the inductance of the circuit.
- 5033. Damping Constant**—The Napierian logarithm of the ratio of two values of an exponentially decreasing quantity separated by unit time. (This is preferred to the term "damping factor.")
- The coefficient "a" appearing in the exponent of the damping factor, ϵ^{-at} , which occurs in expressions of the following forms for damped currents.
- $$i = I_0 \epsilon^{-at}$$
- $$i = I_0 \epsilon^{-at} \cos 2\pi f_n t$$
- In an oscillatory circuit containing resistance, inductance, and capacity in series, $a = R/2L$.
- 5034. Alternating Current**—A current, the direction of which reverses at regularly recurring intervals, the algebraic average value being below zero.
- 5035. Damped Alternating Current**—A current passing through successive cycles with progressively diminishing amplitude.
- 5036. Free Alternating Current**—The damped alternating current which flows in a circuit following the cessation of an impressed voltage.

5037. Forced Alternating Current—The alternating current which flows in a circuit as the result of an impressed alternating voltage and which has the same frequency.

5038. Pulsating Current—A periodic current (that is, current passing through successive cycles), the algebraic average value of which is not zero. A pulsating current is equivalent to the sum of an alternating and a constant amplitude direct current.

5039. Direct Current—A unidirectional current. As ordinarily used, the term designates a practically non-pulsating current.

5040. Hot-Wire Ammeter—(Extension type)—An ammeter dependent for its indications on a change in dimensions of an element which is heated by a current through it.

5041. Thermocouple Ammeter—An ammeter dependent for its indications on the change in thermo electromotive force set up in a thermo electric couple which is heated by the current to be measured.

5042. Vacuum Tube Voltmeter—A device for measuring small voltages consisting of a vacuum tube having an ammeter in its output circuit. The scale deflections are calibrated in terms of the voltage applied to the grid circuit.

5043. Amplifier—A device for increasing the amplitude of electric current or voltage, through the control by the input power of a larger amount of power supplied by a local source to the output circuit.

5044. Voltage Amplification—The ratio of the alternating voltage produced at the output terminals of an amplifier to the alternating voltage impressed at the input terminals. (This term should not be used to describe a process). (See 4022, Amplification Factor).

5045. Current Amplification (of an amplifier)—The ratio of the alternating current produced in the output circuit to the alternating current supplied to the input circuit.

5046. Power Amplification (of an amplifier)—The ratio of the alternating-current power produced in the output circuit to the alternating-current power supplied to the input circuit.

5047. Power Amplifier—An amplifier which is capable of producing relatively large power in an output circuit.

5048. Relay—A device in which the input power is used to control a local source of power in the output circuit.

5049. Regeneration—The process by which a part of the output

power of an amplifying device reacts upon the input circuit in such a manner as to reinforce the initial power, thereby increasing the amplification. (Sometimes called "feed back.")

5050. Attenuation Equalizer—A device for altering the attenuation of a circuit for various frequencies in order to make substantially equal the total attenuation for all frequencies within a certain range.

5051. Transmission Level—The radio field intensity or the signaling power amplitude at any point in a communication system, expressed either in some absolute unit or with reference to an arbitrary base value.

5052. Transmission Unit (Abbreviation TU)—A unit of power ratio used for expressing transmission loss or transmission gain (amplification). Two amounts of power differ by one transmission unit when they are in the ratio of $10^{0.1}$. Two amounts of power differ by N transmission units when they are in the ratio of $10^{(0.1)N}$. The number of transmission units is ten times the common logarithm of the power ratio to be expressed; i. e., $10 \log_{10} \frac{P_1}{P_2}$.

Power Ratio		TU
1	(= 10^0)	0 (= $10 \log_{10} 1$)
1.259	(= $10^{0.1}$)	1 (= $10 \log_{10} 1.259$)
10	(= 10^1)	10 (= $10 \log_{10} 10$)
100	(= 10^2)	20 (= $10 \log_{10} 100$)
1000	(= 10^3)	30 (= $10 \log_{10} 1000$)

For current ratios, the number of transmission units is equal to 20 times the common logarithm of the current ratio (with constant impedance) to be expressed; i. e.,

$$20 \log_{10} \frac{I_1}{I_2}$$

Current Ratio	TU
0.001	— 60.00
0.005	— 46.02
0.01	— 40.00
0.05	— 26.02
0.1	— 20.00
0.2	— 13.98
0.5	— 6.02
1.0	0.00
1.5	3.52

Current Ratio	TU
2	6.02
5	13.98
10	20.00
20	26.02
50	33.98
100	40.00
500	53.98
1000	60.00

- 5053. Loading Coil**—An inductance coil, usually not inductively coupled to any other circuit, for connection in a tuned circuit to decrease its resonant frequency.
- 5054. Choke Coil**—An inductance coil inserted in a circuit to offer reactance to the flow of alternating current components while allowing direct current to pass.
- 5055. Banked Winding**—A form of coil winding in which single turns are wound successively in each of two or more layers, the winding proceeding from one end of the coil to the other, without return.
- 5056. By-Pass Condenser**—A condenser used to provide a path of comparatively low impedance around some circuit element.
- 5057. Stopping Condenser**—A condenser used to insert a comparatively high impedance in some branch of a circuit for the purpose of limiting the flow of low frequency alternating current or direct current without materially affecting the flow of high frequency alternating current.
- 5058. Filter**—A selective circuit network designed to transmit alternating-currents within a continuous band or bands of frequencies and attenuate currents of all frequencies outside the transmission band or bands.
- 5059. Low-Pass Filter**—A filter designed to transmit currents of all frequencies below a critical or cut-off frequency and attenuate currents of all frequencies above this critical frequency.
- 5060. High-Pass Filter**—A filter designed to transmit currents of all frequencies above a critical or cut-off frequency and attenuate currents of all frequencies below this critical frequency.
- 5061. Band-Pass Filter**—A filter designed to transmit currents of frequencies within a continuous band limited by an upper

and a lower critical or cut-off frequency and attenuate currents of all frequencies outside of that band.

- 5062. Rectifier**—A device whose resistance for currents in one direction differs from its resistance for currents in the other direction and which is used to convert an alternating-current wave into a unidirectional wave.
- Note**—In dealing with rectification in the reception of radio signals the term “detector” or “converter” is preferred to “rectifier.” (See 3012, Detector.)
- 5063. Half-Wave Rectifier**—A rectifier which changes alternating current into pulsating, unidirectional current, utilizing only one-half of each cycle.
- 5064. Full-Wave Rectifier**—A double rectifier arranged so that current is allowed to pass in the same direction to the load circuit during each half cycles of the alternating-current supply, one element functioning during one-half cycle and the other during the next half cycle, and so on.
- 5065. Vacuum Tube Rectifier**—A device for rectifying an alternating current by utilizing the electron flow between two electrodes in a vacuum or in a gas.
- 5066. Resonance Transformer**—A transformer with condenser load, whose circuits are adjusted as a whole to have the same frequency as that of the alternating current supplied to the primary, thereby causing the secondary voltage to build up to higher values than would otherwise be attained.
- 5067. Radio-Frequency Transformer**—A transformer for use with radio-frequency currents.
- 5068. Audio-Frequency Transformer**—A transformer for use with audio-frequency currents.
- 5069. Rheostat**—A resistor which is provided with means for readily varying its resistance.
- 5070. Potentiometer**—A device consisting of a resistor provided with a movable or sliding contact in addition to its terminal contacts. It is used as a voltage divider. The current is passed between the terminal contacts and the desired difference of potential is obtained between one terminal contact and the movable contact. (“Voltage divider” is a preferred term.)
- 5071. “A” Battery**—A battery which provides heating current for the filament of a vacuum tube.
- 5072. “B” Battery**—A battery connected in the plate circuit

of a vacuum tube, for the purpose of supplying power to the plate circuit.

- 5073. "C" Battery**—A battery connected in the circuit between the filament and grid of a vacuum tube so as to apply a potential to the grid.
- 5074. Protective Device**—A device for keeping currents or voltages of undesirably large magnitude out of a given part of an electrical circuit. For example, fuse, lightning arrestor.
- 5075. Quality**—(In broadcasting)—The degree to which sound is faithfully reproduced.
- 5076. Transmission-Frequency Characteristic**—The variation with frequency of the transmission efficiency of a circuit or transmission path. (See 1018, Transmission Loss).
- 5077. Distortion**—A change in wave form as in passing through a circuit or transmission medium. A wave form may be distorted by:
- (a) The presence in the output of components having frequencies not present in the original wave due to circuit elements having non-linear characteristics.
 - (b) A change in the relative amplitude of the component frequencies due to variation in the transmission efficiency over the frequency range involved.
 - (c) A change in the relative phase of the component frequencies. (Not a cause of distortion when present in audio-frequency waves).

Two or more of these forms of distortion may exist simultaneously. (See 1020, Fading).

SECTION 6—ANTENNAS

- 6001. Antenna**—A device for radiating or absorbing radio waves.
- 6002. Aerial**—The elevated conductor portion of a condenser antenna.
- 6003. Beam Antenna**—A unilateral directive antenna such that its radiation is substantially confined to a narrow beam.
- 6004. Unilateral Antenna**—An antenna having the property of radiating or receiving radio waves in larger proportion in some one angular region than in all other directions.
- 6005. Bi-Lateral Antenna**—An antenna having the property of radiating or receiving radio waves in larger proportion in angular regions 180 degrees apart than in all other directions.
- 6006. Cage Antenna**—An antenna having conductors which consist of groups of parallel wires arranged as the elements of a cylinder.
- 6007. Coil Antenna**—An antenna consisting of one or more complete turns of wire.
- 6008. Condenser Antenna**—An antenna consisting of two capacity areas.
- 6009. Directive Antenna**—An antenna having the property of radiating radio waves in larger proportion along some directions than others.
- 6010. Directional Antenna**—An antenna having the property of radiating or receiving radio waves in larger proportion along some directions than others.
- 6011. Flat Top Antenna**—An antenna having approximately horizontal conductors at the top.
- 6012. Harp Antenna**—An antenna composed of vertical, or approximately vertical conductors, all in one plane.
- 6013. Inverted Antenna**—A flat top antenna in which the lead-in is taken from one end of the horizontal portion.
- 6014. Multiple Tuned Antenna**—An antenna with connections to ground through inductances at more than one point, the inductances being so determined that their reactances in parallel present a total reactance equal to that necessary to give the antenna the desired natural frequency.
- 6015. Feed Ratio** (of a multiple tuned antenna)—The value obtained by dividing the sum of the currents at all the antinodes by the current in the line feeding the antenna.

- 6016. Series or Feed Resistance** (of a multiple tuned antenna)
—The quotient of the power delivered to the antenna by the square of the current in the line feeding the antenna.
- 6017. T Antenna**—A flat top antenna in which the lead-in is taken from the center of the horizontal portion.
- 6018. Umbrella Antenna**—An antenna, the conductors of which form elements of a cone with the apex at the top to which the lead-in is connected.
- 6019. Wave Antenna**—A horizontal aerial the physical length of which is of the same order of magnitude as that of the signaling waves to be received, and which is so used as to be strongly directional.
- 6020. Antenna Resistance**—An effective resistance which is numerically equal to the quotient of the average power in the entire antenna circuit by the square of the effective current at the point of maximum current.
Note: Antenna resistance includes: Radiation resistance, ground resistance, radio-frequency resistance of conductors in antenna circuit, equivalent resistance due to corona, eddy currents, insulator leakage, dielectric loss, and so on.
- 6021. Effective Height of an Antenna**—The height of an equivalent ideal antenna producing the same radiated field. As ordinarily defined, this ideal antenna is a vertical conductor carrying a uniform current equal to the maximum current existing at any point in the actual antenna.
- 6022. Meter Amperes**—The product of the antenna current in amperes at the point of maximum current and the antenna effective height in meters for any radio transmitting station. It constitutes a factor for indicating the radiating strength of radio transmitting stations.
- 6023. Antenna Form Factor**—The ratio of the effective height of an antenna to its actual physical height.
- 6024. Radiation Resistance**—The quotient of the total power radiated by an antenna by the square of the effective current at the point of maximum current.
- 6025. Radiation Efficiency**—The radiation efficiency of an antenna is the ratio of power radiated to the total power delivered to the antenna, at a given frequency.
- 6026. Fundamental or Natural Frequency** (of an antenna)—The lowest resonant frequency of an unloaded antenna. (Unloaded, i. e., without added inductance or capacity.)

- 6027. Lead-In**—That portion of an antenna system which completes the electrical connection between the elevated outdoor portion and the instruments or disconnecting switches inside the building.
- 6028. Antenna Loading Coil**—A coil, inserted to increase the inductance of the antenna circuit.
- 6029. Counterpoise**—A system of wires or other conductors, forming the lower capacity area of a condenser antenna elevated above and insulated from the ground and substantially as extensive as the aerial.
- 6030. Ground System** (of an antenna)—That portion of the antenna system below the antenna loading devices or generating apparatus most closely associated with the ground and including the ground itself.
- 6031. Ground Wire**—A conductive connection to the earth.
- 6032. Ground Equalizer Inductors**—Coils of relatively low inductance placed in the circuit connected to one or more of the grounding points of an antenna ground system, to divide the current between the various points in any desired way.

SECTION 7—DIRECTION FINDING

7001. Direction Finder (Radio Compass or Goniometer)—

A radio receiving device which permits determination of the line of travel of waves as received from transmitting station.

7002. Direction Finder Calibration—The determination of the direction and amount of local wave front distortion to the end that the true bearing may be determined from the apparent bearing given by the direction finder.

7003. Radio Wave Front Distortion—A change in the direction of advance of radio waves.

7004. Unidirectional Radio Direction Finder (Sense Radio Direction Finder)—A radio receiving device which permits determination of the direction (without 180° ambiguity) of waves as received from a transmitting station.

7005. Radio Beacon—A radio transmitting station in a fixed geographic location which emits a distinctive or characteristic signal for enabling mobile receiving stations to determine bearings.

7006. Equisignal Radio Beacon—A radio beacon which transmits two distinctive signals which may be received with equal intensity only in certain directions.

7007. Equisignal Zone—The region in which the two distinctive signals from an equisignal radio beacon are received with equal intensity.

7008. Observed Radio Bearing—The angular deviation from an arbitrary fixed line, such as the earth's geographical meridian or the fore and aft line of a ship, of the direction of the incoming wave as determined by a radio direction finder (without calibration correction).














7009. Corrected Radio Bearing—An observed radio bearing to which the calibration correction has been applied.

7010. True Radio Bearing—The angular deviation from true North, at the point of observation, of the chord of the great circle passing from the observer, to a given transmitting station.

7011. Fix—The intersection of the lines of direction of two or more bearings.

7012. Balancing Condenser—A condenser used for equalizing the potentials at the terminals of a direction finder coil when set in the position of minimum signal.

STANDARD GRAPHICAL SYMBOLS

Ammeter	
Antenna or Aerial	
Arc	
Battery	
Battery (polarity indicated)	
Buzzer	
Coil Antenna	
Condenser, Fixed	
Condenser, Shielded	
Condenser, Variable	
Condenser, Variable (with moving plate indicated)	
Counterpoise	
Coupler, Inductive (Mutual inductor)	

Coupler, Inductive (with variable coupling)	
Crystal Detector	
Frequency Meter (Wavemeter)	
Galvanometer	
Ground	
Inductor	
Inductor, Iron Core	
Inductor, Variable	
Inductor, Adjustable	
Jack	
Key	
Lightning Arrester	
Resistor	
Resistor, Variable	

Spark Gap, Non Synchronous	
Piezoelectric Crystal	
Spark Gap, Plain	
Spark Gap, Quenched	
Spark Gap, Synchronous	
Telephone Receiver	
Loud Speaker	
Telephone Transmitter (Microphone)	
Thermoelement	
Transformer	
Vacuum Tube, Triode	
Vacuum Tube, Diode	
Voltmeter	
Wires, Joined	
Wires, Crossed not joined	

INDEX

<i>Term</i>	<i>Definition Number</i>	<i>Term</i>	<i>Definition Number</i>
A			
"A" Battery	5071	Band-Pass Filter	5061
Absorption, Atmospheric	1017	Banked Winding	5055
Acceptor	5020	Battery, "A"	5071
Admittance, Input	4038	Battery, "B"	5072
Admittance, Internal Output	4036	Battery, "C"	5073
Aerial	6002	Beacon, Equisignal Radio	7006
Alternating Current	5034	Beacon, Radio	7005
Alternating Current, Damped	5035	Beam Antenna	6003
Alternating Current, Forced	5037	Bearing, Corrected Radio	7009
Alternating Current, Free	5036	Bearing, Observed Radio	7008
Alternator, Radio-Frequency	2019	Bearing, True Radio	7010
Alternator Transmitter	2018	Beat	5016
Anode	4018	Beat Frequency	5017
Ammeter, Hot Wire	5040	Beating	5015
Ammeter, Thermocouple	5041	Bi-Lateral Antenna	6005
Amplification, Current	5045	Broadcasting	2002
Amplification, Power	5046	By-Pass Condenser	5056
Amplification, Voltage	5044	C	
Amplification Factor	4022	"C" Battery	5073
Amplifier	5043	Cage Antenna	6006
Amplifier, Power	5047	Calibration, Direction Finder	7002
Antenna	6001	Capacity Coupling	5026
Antenna, Beam	6003	Capacity, Direct	4031
Antenna, Bi-Lateral	6005	Carrier Current	2005
Antenna, Cage	6006	Carrier Frequency	2006
Antenna, Coil	6007	Carrier Suppression	2007
Antenna, Condenser	6008	Carrier Wave	1010
Antenna, Directional	6010	Cathode	4004
Antenna, Directive	6009	Changer, Frequency	2026
Antenna, Flat Top	6011	Channel, Radio	2012
Antenna, Harp	6012	Characteristic Curve, Emission	4043
Antenna, Inverted L	6013	Characteristic Curve, Grid	4014
Antenna Resistance	6020	Characteristic Curve, Mutual	4040
Antenna, T	6017	Characteristic Curve Plate	4026
Antenna, Umbrella	6018	Characteristic, Transmission-Frequency	5076
Antenna, Unilateral	6004	Choke Coil	5054
Antenna, Wave	6019	Choke Coil, Plate	4027
Arc Converter	2021	Coefficient, Coupling	5023
Attenuation	1019	Coil Antenna	6007
Attenuation Equalizer	5050	Communication, Radio	2001
Atmospheric Absorption	1017	Compass, Radio	7001
Atmospherics	1016	Compensator, Load	2020
Audio Frequencies	5005	Condenser Antenna	6008
Audio-Frequency Transformer	5068	Condenser, Balancing	7012
Autodyne Reception	3004	Condenser, By-Pass	5056
B			
"B" Battery	5072	Condenser, Coupling	5030
Balancing Condenser	7012	Condenser, Grid	4016
Band of Frequencies	2008	Condenser, Stopping	5057
		Condenser Transmitter	2030
		Conductance, Mutual	4023
		Conductance, Plate	4024
		Continuous Waves	1003
		Continuous Waves, Interrupted	1006

<i>Term</i>	<i>Definition Number</i>	<i>Term</i>	<i>Definition Number</i>
D			
Continuous Waves, Key-Modulated	1005	Fading	1020
Continuous Waves, Modulated	1004	Feed Ratio	6015
Control Electrode	4008	Ferromagnetic Modulator	2035
Converter, Arc	2021	Field Intensity, Radio	1010
Counterpoise	6029	Field Intensity, Radio Noise	1012
Coupler	5028		
Coupling	5022	I	
Coupling, Capacity	5026	Filament	4005
Coupling Coefficient	5023	Filament Capacity	4028
Coupling Coil	5029	Filament Current	4007
Coupling Condenser	5030	Filament Voltage	4006
Coupling, Direct	5024	Filter	5058
Coupling, Inductive	5025	Filter, Band-Pass	5061
Coupling, Resistance	5027	Filter, High-Pass	5060
Current Amplification	5045	Filter, Low-Pass	5059
Current, Emission	4042	Fix	7011
Current, Periodic	5013	Flat Top Antenna	6011
Cycle	5001	Forced Alternating Current	5037
E			
Damped Alternating Current	5035	Form Factor, Antenna	6023
Damped Waves	1007	Free Alternating Current	5036
Damping Constant	5033	Frequencies, Band of	2008
Decrement, Logarithmic	5032	Frequencies, Audio	5005
Decremeter	5031	Frequencies, Radio	5006
Detection Coefficient	3013	Frequency	5002
Detection Coefficient, Grid	4015	Frequency Changer	2026
Detection Coefficient, Mutual	4039	Frequency, Group	5007
Detector	3012	Frequency Meter	5009
Diode	4002	Frequency Multiplier	2027
Direct Capacity	4031	Frequency Resonance	5008
Direct Coupling	5024	Full-Wave Rectifier	5064
Direct Current	5039	Fundamental Frequency	5010
Direction Finder	7001	Fundamental Frequency (of an antenna)	6026
Direction Finder, Unidirectional Radio	7004	Fundamental Wavelength	5011
Direction Finder Calibration	7002	G	
Directional Antenna	6010	Gap, Spark	2024
Directive Antenna	6009	Goniometer	7001
Distortion	5077	Grid	4009
Distortion, Radio Wave Front	7003	Grid Capacity	4029
Duplex Operation	2037	Grid Characteristic Curve	4014
F			
Effective Height of an Antenna	6021	Grid Condenser	4016
Electrode, Control	4008	Grid Conductance	4013
Electron Emission	4041	Grid Current	4011
Emission Characteristic Curve	4043	Grid Current, Reversed	4012
Emission Current	4042	Grid Detection Coefficient	4015
Emission, Electron	4041	Grid Filament Capacity	4033
Equalizer, Attenuation	5050	Grid Leak	4017
Equisignal Radio Beacon	7006	Grid-Plate Capacity	4032
Equisignal Zone	7007	Grid-Plate Characteristic Curve	4040
Excitation, Impulse	2025	Grid Potential	4010
G			
		Ground Equalizer Inductors	6032
		Ground System	6030
		Ground Wire	6031
		Group Frequency	5007
H			
		Half-Wave Rectifier	5063
		Harmonic	5012
		Harp Antenna	6012
		Height of an Antenna, Effective	6021
		Heterodyne Reception	3003
		High-Pass Filter	5060
		Homodyne Reception	3005
		Hot-Wire Ammeter	5040
I			
		Impedance, Input	4037
		Impedance, Internal Output	4035
		Impulse Excitation	2025
		Input Admittance	4038

<i>Term</i>	<i>Definition Number</i>	<i>Term</i>	<i>Definition Number</i>
Input Impedance	4037	Plate Capacity	4030
Inductive Coupling	5025	Plate Characteristic Curve	4026
Inductors, Ground Equalizer	6032	Plate Choke Coil	4027
Interference	3016	Plate Conductance	4024
Internal Output Admittance	4036	Plate Current	4021
Internal Output Impedance	4035	Plate-Filament Capacity	4034
Intermediate Frequency	3007	Plate Potential	4020
Inverted L Antenna	6013	Plate Resistance	4025
		Potentiometer	5070
		Power Amplification	5046
		Power Amplifier	5047
		Protective Device	5074
		Pulsating Current	5038
K			
Kilocycle	5003		
		Q	
		Quality (in broadcasting)	5075
		Quenched Gap	2024
L			
Lead In	6027		
Leak, Grid	4017		
Level, Transmission	5051	R	
Load Compensator	2020	Radiate	2003
Loading Coil	5053	Radiation	2004
Leading Coil, Antenna	6028	Radiation Efficiency	6025
Logarithmic Decrement	5032	Radiation Resistance	6024
Loss, Transmission	1018	Radio Communication	2001
Loud Speaker	3015	Radio Frequencies	5006
Low-Pass Filter	5059	Radio-Frequency Transformer	5067
		Radio Transmitting Set	2013
		Ratio, Feed	6015
		Receiver	3001
M		Receiver, Monitoring	3002
Magnetic Modulator	2035	Receiver, Telephone	3014
Master Oscillator	2016	Receiving Set	3001
Megacycle	5004	Rectifier	5062
Meter Amperes	6022	Rectifier, Full-Wave	5064
Microphone	2029	Rectifier, Half-Wave	5063
Modulation	2031	Rectifier, Vacuum Tube	5065
Modulation, Double	2032	Reflex, Circuit	3008
Modulation, Percentage	2033	Regeneration	5049
Modulator	2034	Rejector	5021
Modulator, Ferromagnetic	2035	Relay	5048
Modulator, Magnetic	2035	Resistance, Antenna	6020
Modulator, Vacuum Tube	2036	Resistance Coupling	5027
Monitoring Receiver	3002	Resistance, Plate	4025
Multiple Tuned Antenna	6014	Resistance, Radiation	6024
Multiplier, Frequency	2027	Resistance, Series or Feed	6016
Mutual Characteristic Curve	4040	Resonance Frequency	5008
Mutual Conductance	4023	Resonance, Parallel	5019
Mutual Detection Coefficient	4039	Resonance, Series	5018
		Resonance Transformer	5066
		Rheostat	5069
N		Rotary Gap	2024
Natural Frequency (of an antenna)	6026	Rotary Gap, Synchronous	2024
Noise Field Intensity, Radio	1012		
Noise Ratio, Signal	1013		
		S	
O		Selectivity	3011
Oscillator	2015	Self-Heterodyne Reception	3004
Oscillator, Master	2016	Sense Radio Direction Finder	7004
Oscillatory Circuit	5014	Sensitivity	3010
Output Admittance, Internal	4036	Series Resonance	5018
Output Impedance, Internal	4035	Set, Radio Transmitting	2013
		Side Bands	2009
P		Side-Band Transmission, Single	2011
Parallel Resonance	5019	Side Frequencies	2010
Periodic Current	5013	Signal	1008
Plain Gap	2024		
Plate	4019		

<i>Term</i>	<i>Definition Number</i>	<i>Term</i>	<i>Definition Number</i>
Signal-Noise Ratio	1013	Transmitter, Telephone	2028
Signal Wave	1009	Transmitter, Vacuum Tube	2014
Single Side-Band Transmission	2011	Transmitting Set, Radio	2013
Spark Gap	2024	Tube, Vacuum	4001
Spark Transmitter	2022	Tuning	3009
Speaker, Loud	3015		
Static	1015	U	
Stopping Condenser	5057	Unidirectional Radio Direction Finder	7004
Strays	1014	Unilateral Antenna	6004
Super-Heterodyne Reception	3006	Unit, Transmission	5052
Suppression, Carrier	2007	Umbrella Antenna	6018
Swinging	1021		
Synchronous Rotary Gap	2024	V	
		Vacuum Tube	4001
		Vacuum Tube Rectifier	5065
T		Vacuum Tube Voltmeter	5042
T Antenna	6017	Voltage Amplification	5044
Tank Circuit	2017	Voltmeter, Vacuum Tube	5042
Telephone Receiver	3014		
Telephone Transmitter	2028	W	
Thermionic	4044	Wave	1001
Thermocouple Ammeter	5041	Wave Antenna	6019
Triode	4003	Wave Front Distortion, Radio	7003
Transformer, Audio-Frequency	5068	Wave, Continuous	1003
Transformer, Radio-Frequency	5067	Wave, Damped	1007
Transformer, Resonance	5066	Wave, Interrupted Continuous	1006
Transmission-Frequency Characteristic	5076	Wave, Key Modulated Continuous	1005
Transmission Level	5051	Wave, Modulated Continuous	1004
Transmission Loss	1018	Wavelength	1002
Transmission Unit	5052	Wavemeter	5009
Transmitter	2013	Winding, Banked	5055
Transmitter, Alternator	2018		
Transmitter, Condenser	2030	Z	
Transmitter, Plain Antenna	2023	Zone, Equisignal	7007
Transmitter, Spark	2022		

P BORSI